



GLWA Linear System Integrity Program Update

Jody Caldwell, P.E. Chief Planning Officer

Linear System Integrity Program Key Take-Aways

- ♦ Objective since GLWA inception was to move from reactive to proactive asset management
- **◆**Established the Linear System Integrity Program (LSIP)
- ♦ Significant analysis occurred following the 54-inch main break in February 2025
- ◆Evolution to a more comprehensive "Water Transmission Main Renewal Strategy" is being developed
- **♦** Long-term funding is the biggest challenge (To be continued 10/8)




Water Transmission System

- **◆**Total Transmission Main: 800 miles across eight counties
 - Concrete mains: 500 miles
 - Metallic mains: 300 miles
- Large diameter mains up to 120 inches and under a pressure of 180 pounds per square inch
- ♦ Average age: 76 years
- **◆**Expected useful Life: 80 120 years depending on pipe type




Water Transmission System






The NEED to Proactively Manage Transmission



The NEED to Proactively Manage Transmission Mains





Linear System Integrity Program (LSIP) History



Successful Linear System Management

Successful management, continuing to be affordable and sustainable



Pipeline Risk Management

Scientifically defensible approach to pipeline risk management




Lowest Lifecycle Cost

Use data to drive decision making to manage pipeline risk and optimize maintenance & renewal budgets



LSIP History


- **2017-2020:**
 - Prioritization of transmission main for strategic condition assessment and targeted renewal was developed
 - Developed the strategy to begin "Lean" program:
 - Minimize impacts due to failure of the highest risk mains
 - ♦ High resolution condition assessment In each year, plan one, design one and execute one
 - Approximately 20 miles per year
 - Focus on Prestressed Concrete Cylinder Pipe (PCCP)






LSIP History

- **♦**2021 To Date:
 - ♦ Initiated contract with LSIP Program Manager, HDR of Michigan
 - Updated risk-based prioritization approach
 - Developed program framework, governance and processes
 - Began high resolution condition assessments and renewal








With Actual Condition

Data & Reprioritize






LSIP Progress

- Condition Assessment Completed
 - ♦ Aboveground survey 37.5 miles
 - ♦ High resolution inspection 52 miles
 - ♦ Visual and sounding inspection 17.5 miles
 - ◆ Pilot technologies (external acoustic & internal fiber) 2.4 mile
 - ♦ Opportunistic pipe inspection 13.2 miles
 - Future planned pipe inspection (through 2027) 27 miles









LSIP Progress (Cont'd)



Prestressed
Concrete Cylinder
Pipe (PCCP)
Cross Section

Mortar Coating ~

Concrete Core

Steel Cylinder



LSIP Progress (Cont'd)

- **♦**Pipe segments renewed:
 - Pipes failed (cracks/hollows)- 20 (400 feet)
 - Pipes with significant distressed 57 (1,043 feet)
 - Pipes nearing or exceeding strength limit– 97 (1,939 feet)
 - Pipes under the influence of cathodic protection system – 33 (632 feet)







LSIP Progress (Cont'd)

- **♦**Pipe segments renewed:
 - Primary renewal strategy has been with Carbon Fiber Reinforced Polymer (CFRP) (3,785 feet)





Then GLWA's World Changed February 17, 2025









Then GLWA's World Changed February 17, 2025










54-Inch Failure Investigation

- Metallurgical Analysis Conclusions:
 - Welding defects
 - Lack of fusion
 - Inadequate penetration
 - Low toughness properties
 - Corrosion causing:
 - Significant thinning of external weld of longitudinal seam
 - ◆ Large, discrete, external pits on pipe section away from the rupture location were observed






Photograph of the pipe section after removal from the flatbed truck. The tape measure shows the distance, in feet, downstream (D/S) from the upstream (U/S) cut end of the pipe section. The location where a metallographic mount was removed is identified by the blue rectangle.



Ongoing 54-Inch Renewal Investigation

- Inspection and assessment of transmission main for design of the renewal
 - Alternative slip lining approaches being considered
- Hydraulic modeling performed to determine possibility of decommissioning portions of the main
- Multiple field investigations (valve closures) continue to:
 - Determine extent of possible decommission and renewed sections
 - Evaluate redundancy options for water supply
- Initial determination that perhaps not all of this transmission main is needed to meet service levels







Pilot Electromagnetic Remote Field Testing


(RFT) Technology

- **♦** RFT technology
 - Technology is only used on dewatered transmission mains
 - The device is brought into the pipe through access manways and reconstructed
 - The device is tethered and pulled through the pipe
 - Measures remaining pipeline wall thickness for metallic pipe
 - Possible identification of defects of the weld.

PICA RFT Series







Pilot Electromagnetic Remote Field Testing (RFT) Technology


• Currently planning and design of a pilot:

• ½ mile section the 54-Inch

• Portion of main currently out-of-service

• Sequencing and schedule still to be

determined





Identification of Other Welded Steel Pipes

- **♦** Identification of other welded steel transmission main
 - Research as-built drawings, field reports and other documentation
 - Research era that welded steel pipelines was the primary method of construction
 - Determined to be between 1928 1939
 - It is believed that steel pipelines with unconfirmed construction method that are constructed in this period are welded steel
- ◆ Planning & design of condition assessment of these mains
 - Primary technology is inline leak detection
 - Technology will not identify the condition of the weld, but will generally identify the condition of the main
 - As leaks are investigated and repaired, a more detailed assessment of the main can be made

IISTORY factories, tools, equipment, thips, skystrapers, sina JCTION steel, pentacks, steel pipe for water as well as go oil service.

Jet be brean about 1000 R.C. The Old Five years after the historic 1849 Gold Ru

The Age of from began about 1000 B.C. The Old Testament mentions iron 90 times. The Romans used iron throughout their empire and built the first Roman aqueduct in 312 B.C. requiring a considerable distri-

Five years after the historic 1849 Gold Rush in California, the Francis Smith Company established a dup in the mining town of Grass Valley, California, to produce water pipe for the gold miners. The pipe was

History of Steel Water Pipe

Its Fabrication and Design Development


Prepared by Walter H. Cates, Civil Engineer-Hydraulics





Planned Inline Leak Detection

Welded Steel - 1928-1939	Length (Miles)
A: Springwells Water Treatment Plant to W Jefferson (Beard Street 54")	4.7
B: Springwells Water Treatment Plant to 175 via 8 Mile Road	11.0
C: Clarita/Washburn to Nevada/Carrie	7.2
D: Springwells Water Treatment Plant to Hazelton/Joy Rd	7.3
E: Springwells Water Treatment Plant to Wisconsin/Belton	0.6
Total	30.8






54-Inch Renewal Investigation Follow-Up

Process

- Requires taps at insertion and extraction locations
- Insert device into a live transmission main
- Carried along the pipe with the flow of water
- "Listens" for leaks in the pipe
- As the device travels along the pipe, valves at connected mains must be closed
- ♠ Coordination and communication strategy will be developed with DWSD
- Inline leak detection is currently under planning and design
- Sequencing and schedule still to be determined





Evolution of the Linear System Integrity Plan

- **♦** Evolve LSIP to a more comprehensive renewal strategy by considering:
 - Decommissioning 127 miles of candidate water main
 - Renewing/replacing pipelines exceeding their useful life primarily metallic pipe
 - Continuing Prestressed Concrete Cylinder Pipe inspections and renewal
 - ◆ Updating prioritization to better account for flooding impacts to public health & safety



Linear System Integrity Program Key Take-Aways

- **♦**Objective since GLWA inception was to move from reactive to proactive
- **◆**Established the Linear System Integrity Program (LSIP)
- ♦ Significant analysis occurred following the 54-inch main break in February 2025
- ◆Evolution to a more comprehensive "Water Transmission Main Renewal Strategy" is being developed
- **♦** Long-term funding is the biggest challenge (To be continued 10/8)



